

Safety Data Sheet for 450

1. IDENTIFICATION OF PRODUCT and COMPANY

PRODUCT NAME - CONCEPT NEW MILLENIUM, NEW & USED CAR POLISHES

PRODUCTS COVERED - 426, 447, 448, 449, 450, 462, 495, 926

INTENDED USE - For professional use only. For Professional Use ONLY.

SUPPLIER - Concept Chemicals & Coatings P.O. Box 9, Bramhall, Stockport, Cheshire. SK7 1JF

Emergency Tele. - 0161-335-0213

2. COMPOSITION/INFORMATION of INGREDIENTS

10-25 % NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (CONTAINS <0.1 BENZENE)

Symbols Xn Risk Phrases 65

2.5-10 % PETROLEUM DISTILLATE, LOW AROMATIC (CONTAINS <0.1% BENZENE)

Symbols Xn Risk Phrases 65

Symbols Key - T=Toxic Xn=Harmful C=Corrosive Xi=Irritant E=Explosive O=Oxidising F+=Extremely Flammable

F=Highly Flammable N=Environmentally Hazardous

Details of Risk Phrases

R65 Harmful: may cause lung damage if swallowed.

3. HAZARDS IDENTIFICATION

HAZARDS

Flammable

RISKS

Flammable

SAFETY ADVICE

Avoid contact with the skin

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

FURTHER ADVICE

Eye irritation may result if splashed into eyes. Skin irritation may result if exposed to skin. Gastric discomfort may result if swallowed. May be harmful if swallowed. May irritate Respiratory System.

4. FIRST AID MEASURES

ACTION ON INHALATION - Remove to fresh air, keep warm and at rest. If breathing is irregular or stopped give artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

ACTION ON SKIN CONTACT - Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner, do NOT use solvents or thinners.

ACTION ON EYE CONTAMINATION - Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 mins. holding the eyelids apart, seek medical advice.

ACTION ON SWALLOWING - If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

GENERAL FIRST AID ADVICE - In all cases of doubt or when symptoms persist seek medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

RECOMMENDED EXTINGUISHING MEDIA - Alcohol Resistant Foam, Carbon-Dioxide, Dry Powder, Water Spray Mist, Foam, Halogenated Hydrocarbons.

DO NOT USE - .

FIRE FIGHTING INSTRUCTIONS - Fire will produce smoke containing hazardous products of combustion (see Section 10). Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with a water spray. Do not allow run off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in sect. 7&8. Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth and place in suitable container for disposal in accordance with the waste regulations. Clean preferably with a detergent, avoid use of solvents. Do not allow to enter drains or water courses. If it does the local water company should be contacted immediately, in case of contamination of streams rivers or lakes the National Rivers Authority

7. STORAGE AND HANDLING

STORAGE PRECAUTIONS - If designated flammable is subject to the Highly Flammable Liquids & Liquefied Petroleum Gases Regulations. Up to 50lts may be kept in workroom fireproof cupboard or bin, otherwise in a separate room. Observe the label precautions. Store between 5 & 25°C in a dry well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are opened should be properly resealed and kept upright to prevent leakage. Store away from oxidising agents and strongly alkaline and acidic materials. The principles contained in the HSE's guidance note Storage of Packaged Dangerous Substances should be observed when storing this product.

HANDLING PRECAUTIONS - Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent creation of explosive or flammable mixtures and avoid vapour concs higher than the OEL. Do not use in areas where potential sources of ignition exist. Electrical equipment should be protected to the appropriate standard. Use non sparking tools & exclude sources of heat, sparks & flames. Avoid skin & eye contact. For personal protection see Sect.8. Good housekeeping and regular removal of waste materials will minimise risks. The Manual Handling Operations Regulations 1992 may apply to the handling of containers of this product. Refer to the published guide weight when carrying out assessments. The requirements of regulations made under the Health & Safety at Work etc. 1974 should be complied with.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

NO CHEMICALS PRESENT WITH EXPOSURE LIMITS

ENGINEERING PRECAUTIONS - Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If extraction methods are insufficient to maintain concentrations of particulates and/or solvent vapours below relevant OEL's, suitable respiratory protective equipment should be worn.

GENERAL PRECAUTIONS - All personal protective equipment should conform to the Provision & Use of PPE Regulations 1992.

RESPIRATORY PROTECTION - If exposure to hazardous substances identified above cannot be controlled by provision of local exhaust ventilation & good general extraction, suitable respiratory protective equipment should be worn.

HAND PROTECTION - Full physical protection is best. Seek relevant advice from glove manufacturers. Barrier cream may be of help but should not be applied after exposure has occurred.

EYE PROTECTION - Eye protection designed to protect against liquid splashes should be worn.

SKIN PROTECTION - Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap & water or a proprietary skin cleaner.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State - Liquid

Flash Point

Specific Gravity - 1

Vapour Density - HEAVIER than AIR

Solubility in Water - MISCIBLE

10. STABILITY AND REACTIVITY

Stable under the recommended storage & handling conditions (see Sect.7). In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, and oxides of nitrogen may be produced. Keep away from oxidising agents and strongly alkaline and acid materials to prevent the possibility of an exothermic reaction.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself. Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and respiratory system and adverse effects on the renal and central nervous systems. Symptoms include headaches, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases unconsciousness. Splashes in the eyes may cause irritation and reversible local damage. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Ingestion will result in irritation of the gastrointestinal tissues resulting in pain, vomiting, abdominal tenderness, nausea, blood in vomit & faeces.

12. ECOLOGICAL INFORMATION

There is no data available on the product itself. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters. The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution (1974) & Environmental Protection (1990) Acts. Using the information in this data sheet, advice should be obtained from the Waste Regulation Authority whether the Special Waste Regulations 1980 apply.

14. TRANSPORT INFORMATION

UN No - 1268

Packing Group - III

Class - 3.3

Designation - FLAMMABLE LIQUID

For Transport Information other than UK Road or Rail please contact your supplier.

REGULATORY INFORMATION

CLASSIFICATION

Flammable

CONTAINS

RISKS PHRASES

Flammable

SAFETY PHRASES

Avoid contact with the skin

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

16. OTHER INFORMATION

Date of Origination - 27/02/96

Date of Last Revision - 28/07/00

Reason for Revision -

The information contained in this safety data sheet is provided in accordance with the requirements of the Chemicals (Hazard Information & Packaging) Regulations. The product should not be used for purposes other than those shown in sect.1 without first referring to the supplier and obtaining written instructions. As the specific conditions of use of the product are outside of the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this Safety Data Sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Further information and relevant advice can be found in:-

The Control Of Substances Hazardous to Health Regulations 1988 (SI 1988: 1657)

The Manual Handling Operations Regulations 1992 (SI 1992: 2793)

Storage of Flammable Liquids in Containers. HS(G)51

Storage of Packaged Dangerous Substances. HS(G)71

The Environmental Protection (Duty of Care) Regulations 1992 (SI 1988: 2839)